

HSF 禁止使用1级环境管理物质

Approve Sign

Note:

Materials:

.Plunger: Brass 15u" Au over 50u" Ni

.Barrel: Brass 15u" Au over 50u" Ni

.Spring: SUS insulate coating

Mechanical:


.Contact force: 60g±15g at 0.7mm working stroke

.Life test: 20,000 cycles

Electrical(working stroke):

.Rated current & voltage: DC12V; 5A

.Contact resistance: 50 milliohm Max.



SCALE	10:1	UNIT:mm	THIS DOCUMENT IS THE SOLE PROPERTY OF CFE CORPORATION CO.,LTD., AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.	
ANGEL	$\pm 1^\circ$	A4	SHEET: 1 of 1	
0.000	± 0.02		PART NO. BP03816	
0.00	± 0.05	DRAW	FILE NAME BP03811	
0.0	± 0.10	CHECK	TITLE. Pogo pin connector	
GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO		

CFE 东莞市川富电子有限公司
CFE CORPORATION CO.,LTD.

ECN(DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO
	A0	2013.08.14	NEW		