

1

2

3


4

Note:
 Materials:
 .Plunger: Brass 0.125um Au over Ni
 .Barrel: Brass 0.125um Au over Ni
 .Spring: SUS 304 Au
 Mechanical:
 .Contact force: 40g±20g at 0.5mm working stroke
 .Life test: 20,000 cycles
 Electrical:
 .Rated current & voltage: DC 12V; 1A
 .Contact resistance: 50 milliohm Max.

To ensure the best usage, please operate it based on the working height.
 Based on the engineering drawings, shall not exceed the maximum allowed compression.



Approve Sign



BOM		
Part	NO.	Qty
Plunger	M200-P2005	1
Barrel	B518-B1005	1
Spring	M200-S1001	1

ECN(DCN) NO.	REV	DATE	DESCRIPTION
_____	A1	2015.12.09	NEW
_____	A0	2015.11.26	NEW

SCALE	10:1	UNIT:mm	THIS DOCUMENT IS THE SOLE PROPERTY OF CFE CORPORATION CO.,LTD., AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.	东莞市川富电子有限公司 CFE CORPORATION CO.,LTD.
ANGEL	±2°	A4		
0~6	±0.10		SHEET: 1 of 1	
6~30	±0.20	DRAW		PART NO. BP51811
30~150	±0.30	CHECK		FILE NAME BP518XX
GENERAL TOLERANCE UNLESS OTHERWISE NOTED	APPRO			TITLE. Pogo pin